

# ELECTRIC REACH TRUCK " CQD 10,15 L, M "

Model		CQD10L	CQD15L	CQD10M	CQD15M
Power		Electric		Electric	
Operation type		Standing		Seated	
Capacity distance	Q(kg)	1000	1500	1000	1500
Lift height	h3(mm)	3000/5000/6200		3000/5000/6200	
Load centre distance	c(mm)	500		500	
Wheelbase	y(mm)	1380/1480/1480	1480	1480	
Service weight	kg	2140/2540/2640	2340/2740/2840	2200/2600/2700	2400/2800/2900
Tyre type		Polyurethane		Polyurethane	
Height, mast lowered	h1(mm)	2086/2240/2640		2086/2240/2640	
Height, mast extended	h4(mm)	3800/5800/7000		3800/5800/7000	
Height of overhead guard (cabin)	h6(mm)	2200		2114	
Stand height	h7(mm)	295		920	
Overall length	l1(mm)	2360		2390	
Overall width	b1(mm)	1020		1100	
Fork dimensions	s/e/l(mm)	36/100/1070	40/100/1070	36/100/1070	40/100/1070
Fork-carriage width	b3(mm)	660		928	
Aisle width for pallets 1000×1200 crossways	Ast(mm)	2800		2800	
Aisle width for pallets 800×1200 lengthways	Ast(mm)	2850		2850	
Turning radius	Wa(mm)	1700		1740	
Travel speed, laden/unladen	Km/h	7/7.2		7/7.2	

Lift speed, laden/unladen	m/s	0.19/0.2	0.19/0.2
Lowering speed, laden/unladen	m/s	0.5/0.4	0.5/0.4
Service brake		Mechanical	Mechanical
Battery voltage, nominal capacity K5	V/Ah	48/400	48/400
Battery weight	kg	550	550
Battery dimensions l/w/h	mm	983x404x630	1092x336x650
Type of drive control		DC/AC	DC/AC

**\* Specifications and Dimensions are subject to change without notice.**

