

FULL ELECTRIC STACKER

MODEL		PSK 100								PSK 100/3.4 CW	PSK 100/3.5 RW
SPECIFICATIONS											
MAX. CAPACITY (kg)		1000								1000	1000
LOAD CENTER (mm)	A	Fixed 600 // Adjustable 500								500	600
MAX.LIFTING HEIGHT (mm)	B	1600	2000	2500	3000	3350	3500	4000	5000	3400	3500
FREE LIFT (mm)		----		100			280			280	-
MIN. LIFTING HEIGHT (mm)	C	Fixed 95 // Adjustable 85								65	85
MIN. OVERALL HEIGHT (mm)	D	1980	2380	1800	2040	2230	2310	2590	3250	2485	2250
MAX. OVERALL HEIGHT (mm)	D	2410	2810	2950	3810	4160	4310	4810	5810	4050	3980
OVERALL LENGTH (mm)	E	2020		2050				2070		2550	3330 / 3930
OVERALL WIDTH (mm)	F	950						1150		870	1000
FORK OUTER WIDTH (mm)	G	Fixed 590 / 750 // Adjustable 810								800	650
FORK WIDTH (mm)	I	Fixed 180 // Adjustable 100								100	100
FORK LENGTH (mm)	H	Fixed 1160 // Adjustable 1000								1000	1200
MAX. LIFTING SPEED		5 m/min								7.2 m/min	7.2 m/min
LIFT MOTOR		1500-2000W 12V								2000W 24V	2000W 24V
TURNING RADIUS (mm)	R	1650		1680			1700			2650	3600 (Min)
MAX. TRAVELLING SPEED		5 km/h								5 km/h	5 km/h
DRIVE MOTOR		800W 12V								1300W 24V	1700W 24V
SPEED CONTROL TYPE		ELECTRONIC CONTROL								ELECTRONIC CONTROL	
PARKING BRAKE		SPRING, RELEASE BY SOLENOID								SPRING, RELEASE BY SOLENOID	
SAFETY SPEED HEIGHT LIMIT		OVER 500 mm								OVER 400 mm	OVER 400 mm
REACTION BATTERY CAPACITY		12V 300A/h (5hr Operation Time)								220A/h (5h Operation Time)	220A/h (5hr Operation Time)
BATTERY WEIGHT (kg)		154								220	220
FRONT WHEEL (mm)		Ø 78 X 70 (2 pcs)								Ø 200 x 70 (2 pcs)	Ø 200 X 70 (2 pcs)
SWIVEL WHEEL (mm)		Ø 180 X 55 (2 pcs)								Ø 300 x 100	Ø 350 X 100
DRIVE WHEEL (mm)		Ø 240 X 75 (1 pcs)								1600	
APPROXIMATE WEIGHT (kg)		630	660	700	730	760	790	840	1050	1600	1550

* Specifications and Dimensions are subject to change without notice.

REMARKS : CUSTOMISED DESIGNS AVAILABLE ON REQUEST AND MADE TO ORDER

หมายเหตุ : สามารถสั่งทำตามความต้องการ และความเหมาะสมของงาน

